

# rbs Tanking Membrane Primer

Bitumen Solution that Aids Adhesion to Substrate

## DESCRIPTION

rbs Tanking Membrane Primer is a low viscosity one-part bituminous solution for brush or spray application. The solution, designed to aid adhesion to the substrate, is specially formulated to be compatible with the logco range of self adhesive gas resistant, water and vapour proof membranes.

## ADVANTAGES

- Surfaces should be clean and free from all oil, grease, dirt, dust and loose debris.
- On metal surfaces all loose rust must be removed by wire brushing and where advanced signs of corrosion are evident these areas should initially be treated with a rust remover/ inhibitor.
- Surfaces should be clean and dry, however, rbs Tanking Membrane Primer will adhere to damp but not wet surfaces.
- Apply by brush or spray evenly in one generous coating.
- rbs Tanking Membrane Primer is resistant to rainfall within 20 – 30 minutes of its application.

N.B. In order to comply with BS8217: 1994 it is essential that after priming concrete or screeded surfaces the coating is completely free of all solvent and thus a safe drying margin of 2 hours should be allowed.

## APPLICATION

Use only in dry weather and in well ventilated conditions. Surfaces must be absolutely dry.

Never use an atomising spray on wet or damp surfaces nor at temperatures below 3°C.

Apply generously by brush, roller or non-atomising spray. Drying time at 20°C will be about 2 hours.

## TECHNICAL DATA

|                                     |                                                                      |
|-------------------------------------|----------------------------------------------------------------------|
| Specific Gravity @ 15.6c            | 0.89+/- 0.02                                                         |
| Flash Point                         | >32C                                                                 |
| Drying Time                         | Normally touch dry after 30 minutes, completely dry after 75 minutes |
| Solidification Temp (LT Grade only) | <-10C                                                                |
| Coverage                            | 6-8m <sup>2</sup> per litre                                          |

## HEALTH & SAFETY

rbs Tanking Membrane Primer is flammable (flash point >32C). Suitable protective clothing, gloves or gauntlets as well as safety glasses should be worn. Accidental contact with the skin should be removed by washing with soap and water.

Contact with the eyes should be avoided. If accidental contact should occur immediately wash the eyes with copious amounts of water and medical attention must be sought.

## PACKAGING

rbs Tanking Membrane Primer is available in 5, 25 and 200 lt. containers.

## STORAGE

Shelf life is indefinite in tightly sealed, undamaged containers.

## IMPORTANT NOTE

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.